Global Ventures Australia

ABN 77 065 255 763

Eco-Core Moso Bamboo Tambour Faced Panel laminated on White Birch Multiply PRE-FINISHED DATA SHEET

SECTION 1 COMPANY IDENTIFICATION

Company Name	Global Ventures Australia Pty Ltd
Address	Unit 13 / 22 Beaumont Road Mount Kuring Gai NSW 2080 Australia
Phone	+ 61 2 9457 7171
Website	www.ecocore.com.au
Email	enquiries@globalventures.com.au

SECTION 2 PRODUCT

Product Identification	
Product Name	Eco-Core Moso Bamboo Tambour Faced Panel laminated on White Birch Multiply PRE-FINISHED
Timber Species	Russian Birch Plywood, Bamboo
Description	Moso Tambour is bamboo in a flexible mat form, often applied to cover a substrate panel. The Bamboo Tambour strips are connected by taping the backside and attached to a fabric backing. Transforming the bamboo stem is done by cutting it lengthwise into strips and the outer green skin removed. The strips are then treated against mould and insects and boiled (steamed) so sugars are burned off turning the material into a caramel brown colour. The strips are kiln dried, pressed and glued together under high pressure.

SECTION 3 SIZE

Panel Size	3.5, 7, 17 and 7&17mm alternating strips 2440mm x 1220mm x 11, 14, 17, 20, 23, 29, 37, 42 and 46mm, laminated on one side, long grain 2440mm x 1220mm x 10, 13, 16, 19, 22, 28, 34, 39, and 44mm, laminated on two sides, long grain.
	50mm strips 2440mm x 1220mm x 12, 15, 18, 21, 24, 30, 33, 39, and 45mm, laminated on one side, long grain 2440mm x 1220mm x 12, 15, 18, 21, 24, 30, 36, 42, and 48mm, laminated on two sides, long grain.

SECTION 4 CONSTRUCTION

Construction	The bamboo tambour mats are laminated on to the White Birch Multiply with low formaldehyde adhesive. Only the bamboo tambour faces are pre-finished, the edges and backing are raw and un finished.
--------------	---

SECTION 5 COLOUR

Core	Light tan to dark tan inner core
Outer layer	Natural or Caramel, pre finished

SECTION 6 GLUE

Glue	Phenolic glue White Birch Multiply, low formaldehyde glue

SECTION 7 DENSITY

Density	Approximately 680 -700 kg/m3

SECTION 8 ENVIRONMENT

Environment	E0 Certified Core, White Birch Multiply

SECTION 9 APPLICATION

Application	Doors, wall and ceiling panels, shelving, cabinet doors, furniture joinery.