

Global Ventures Australia

ABN 77 065 255 763

Eco-Core SVL (Solid Veneer Lumber) Faced Panel on White Birch Multiply DATA SHEET

SECTION 1 COMPANY IDENTIFICATION

Company Name	Global Ventures Australia Pty Ltd
Address	Unit 13 / 22 Beaumont Road Mount Kuring Gai NSW 2080 Australia
Phone	+ 61 2 9457 7171
Website	www.ecocore.com.au
Email	enquiries@globalventures.com.au

SECTION 2 PRODUCT

Product Identification

Product Name	Eco-Core SVL (Solid Veneer Lumber) Faced Panel on White Birch Multiply
Timber Species	European Beech faces, European Birch core
Description	The Eco-Core SVL Faced Panel is made from approximately 3mm thick SVL laminated onto Eco-Core White Birch Multiply. It can be supplied laminated on one or both faces depending on the requirement. The thinly sliced SVL is stable when pressed on a substrate as there is less movement of the SVL faces. The advantage of using this product in some applications is that it can be supplied in thinner panels.

SECTION 3 SIZE

Panel Size	SINGLE SIDED 2500mm x 1250mm x 25, 28, 34mm DOUBLE SIDED 2500MM x 1250mm x 14, 20, 26, 32, 38mm
-------------------	--

SECTION 4 CONSTRUCTION

Construction	The Eco-Core SVL Faced Panel is supplied raw, sanded to grit 60, long grain. It is a cladding material where exposed edges may require a finishing strip, supplied separately. In the raw product small holes and cracks can occur on the faces caused by open knots, cracks or similar. These holes and cracks are not classified as defects and should be puttied with timber putty prior to fine sanding. It is not supplied to exact measurement, please allow for cutting or fine sanding to finished size.
---------------------	--

SECTION 5 COLOUR

Colour	Light beige, light brown to medium brown.
---------------	---

SECTION 6 GLUE

Glue	phenolic and moisture resistant polyurethane glues
-------------	--

SECTION 7 DENSITY

Density	Approximately 680 -700 kg/m3
----------------	------------------------------

SECTION 8 ENVIRONMENT

Environment	E0 Certified
--------------------	--------------

SECTION 9 MOISTURE

Moisture	Moisture content approximately 10-12%
-----------------	---------------------------------------

SECTION 10 FIRE PROPERTIES

Fire Indices	Available as a separate document, please forward your enquiry to Global Ventures.
---------------------	---

SECTION 11 APPLICATION

Application	Large window/door frames, long span shelving, wall panelling, ceiling cladding, dividers/partitioning, bedroom/office doors, cabinetry, table/bench tops, furniture, joinery work, flooring and more. The appearance of an Eco-Core SVL, SVL Faced Panel and SVL Flooring sample is indicative only. Color, grain and laminations can vary and are not classified as defects. Small samples do not always represent what a large surface will look like.
--------------------	--
