

TECHNICAL DATA SHEET

ECO-CORE® SVL FACED PANEL laminated on Falcata Blockboard

PRODUCT

The Eco-Core SVL (Solid Veneer Lumber) Faced Panel is made from approximately 3mm thick SVL laminated onto both faces of Eco-Core Falcata Blockboard. The SVL Faced Panel on Falcata Blockboard is suitable for use on over-sized doors.

SIZE - AVAILABLE GOOD ONE SIDE OR GOOD TWO SIDES, LONG GRAIN

SINGLE CORE

3030mm x 1210mm x 22, 24, 27, 34mm

TRIPLE CORE

3030mm x 1210mm x 44, 46, 51, 56, 65, 79mm

CONSTRUCTION

The SVL Faced Panel is supplied raw, sanded to grid 60. Exposed edges will require finishing with an edge strip. In the raw product small holes and cracks can occur on the faces caused by open knots, cracks or similar. These holes and cracks are not classified as defects and should be puttied with timber putty prior to fine sanding. These panels are custom made and supplied in full sheets, please give allowance for cutting or fine sanding to exact measurement.

SPECIES/COLOUR

European Beech, Light Beige to Light Brown

GLUE

Phenolic glue, moisture resistant PVA glue

DENSITY

Approximately 350- 430 kg/m³

FIRE RESISTANCE

A full fire test report can be supplied separately, please forward your enquiry.

ENVIRONMENT

E0 Certified

APPLICATION

Doors, cabinetry, large window/door frames and long span shelving, dividers/partitioning, table/bench tops, furniture, joinery work.

The appearance of an SVL Faced Panel is indicative only. Color, grain and laminations can vary and are not classified as defects. Small samples do not completely represent what a large surface will look like.